

## 12K HD ADJUSTABLE CL12A & CL12A-LC

Our 12,000 lbs. capacity 2-Post lift can accommodate a wide range of standard cars, trucks, vans, and SUVs within the same service bay. Standard features include 3-Stage front and rear arms.

Our CL12A-LC can be installed in shops with 12' ceilings.

### SERVICE BAY SPECIFICATIONS

-  **HEIGHT:** 13' 3" minimum
-  **WIDTH:** 14' recommended
-  **DEPTH:** 24' recommended
-  **POWER:** 208-230v, 1pH, 30a



| MODEL NUMBER             | CL12A-LC   | CL12A-LC-DPC-QC                  | CL12A            | CL12A-DPC-QC                  |
|--------------------------|--|----------------------------------|------------------|-------------------------------|
| Description              | Low-Ceiling  | Low-Ceiling w/ DPC & QuickCycle™ | Standard         | Standard w/ DPC & QuickCycle™ |
| Lifting Capacity         | 12,000 lbs.  |                                  |                  |                               |
| Lift Configuration       | Symmetric  |                                  |                  |                               |
| Arm Configuration        | 3-Stage Front & Rear                               |                                  |                  |                               |
| Rise Height              | 80¾"   |                                  | 84¾"             |                               |
| Overall Height           | 11' 11"  |                                  | 13' 8" or 13' 2" | 13' 8" or 13' 2"              |
| Overall Width            | Standard - 11' 10"   +6" - 12' 4"   +12" - 12' 10" |                                  |                  |                               |
| Drive Thru Clearance     | Standard - 8' 7½"   +6" - 9' 1½"   +12" - 9' 7½"   |                                  |                  |                               |
| Floor to Overhead Switch | 11' 4½"  |                                  | 13' 2" or 12' 8" | 13' 2" or 12' 8"              |
| Arm Reach                | Min. 27½" Max. 59"                                 |                                  |                  |                               |
| Screw Pad Height         | Min. 5" Max. 12⅝" (includes 6" stack adapter)      |                                  |                  |                               |
| Rise Time                | 60s  | 38s                              | 63s              | 40s                           |
| Min. Ceiling Height      | 12'  |                                  | 13' 9" or 13' 3" | 13' 9" or 13' 3"              |

